


### Terrace outlets TOPWET TWT

#### BASIC INFORMATION


<b>purpose</b>	drainage of flat roofs, terraces and balconies
<b>material</b>	polyamide PA6
<b>integrated connection sleeve</b>	BIT – modified bitumen strip SBS, PVC – mPVC based foil, TPO – thermoplastic (flexible) polyolefin, EPDM – synthetic rubber foil, PE – polyethylene foil, STE – a sleeve for connecting of waterproofing screed
<b>colour</b>	orange
<b>load category</b>	H 1,5
<b>certification</b>	EN 1253-2:2015 - Gullies for buildings - Part 2: Roof drains and floor gullies without trap
<b>manufacturer</b>	TOPWET s.r.o., náměstí Viléma Mrštíka 62, 664 81 Ostrovačice, Czech Republic

#### TECHNICAL PARAMETERS



#### Terrace outlets – vertical version

Type	DN	Dimensions [mm]						
		a	b	c	d	e	f	g
TWT 75 S	70	204	182	80	75	27	133	156
TWT 110 S	100	204	182	80	75	27	133	156
TWT 125 S	125	204	182	80	75	27	133	156



#### Terrace outlets – horizontal version

Type	DN	Dimensions [mm]			
		a	b	c	d
TWT 50 V	50	204	92	225	44
TWT 75 V	70	204	102	225	28
TWT 110 V	100	204	143	238	33
TWT 125 V	125	204	143	238	26