




Attachments for thermal insulation for terrace outlets TOPWET TWTN

BASIC INFORMATION

purpose	for drainage of terraces and balcon
material	polyamid PA6
integrated connection sleeve	BIT – modified bitumen strip SBS, PVC – mPVC based foil, TPO – thermoplastic (flexible) polyolefin, EPDM – synthetic rubber foil, PE – polyethylene foil, STE – a sleeve for connecting of waterproofing screed
colour	orange
load category	H 1,5
certification	EN 1253-2:2015 - Gullies for buildings - Part 2: Roof drains and floor gullies without trap
manufacturer	TOPWET s.r.o., náměstí Viléma Mrštíka 62, 664 81 Ostrovačice, Czech republic
documents (name, number, date, issued by - name and adress)	Bescheinigung Nr. 7312223-01z ze dne 29. 11. 2012, vydal TÜV Rheinland LGA Products GmbH, Dreikronenstraße 31, 97082 Würzburg

TECHNICAL PARAMETERS



Dimensions of the attachments for terrace outlets

Type	for terrace outlets		Dimensions [mm]				
	TWT / TWTE		a	b	c	d	Insulation thickness
TWTN v300	75, 110, 125		204	130	370	20	20–300

All outlet attachments can be made and supplied to order in a heated version